
IMPLEMENTATION OF AND COMPLIANCE WITH THE ENVIRONMENTAL MANAGEMENT PLAN FOR THE MINING OF SAND AND QUARRYING FOR CONSTRUCTION MATERIALS BY NAMIBIA CONSTRUCTION (PTY) LTD ON THE REMAINDER OF PORTION 9 OF FARM KRUMHUK NO. 30, KHOMAS REGION, NAMIBIA



13 February 2020

Prepared by:

environmental consulting

Prepared for:



CONTACT DETAILS



Mr W.J. Schmidt Contract Manager Namibia Construction (Pty) Ltd P.O. Box 5092 Windhoek Namibia

Tel: +264 61 237187/8 Fax: +264 61 233784

E-mail: wilfried.schmidt@namibiaconstruction.com



Dr Lima Maartens LM Environmental Consulting P.O. Box 1284 Windhoek Namibia

Tel: +264 61 255750 Fax: 088 61 9004 E-mail: lima@iwav.na

Declaration: LM Environmental Consulting is an independent consulting firm with no interest in the project which is the subject matter hereof other than to fulfil the contract between the client and the consultant for delivery of specialised services as stipulated in the terms of reference.

Limitation of liability: LM Environmental Consulting accept no responsibility or liability in respect of losses, damages or costs suffered or incurred, directly or indirectly, under or in connection with this report to the extent that such losses, damages, and costs are due to information provided to LM Environmental Consulting for purposes of this report that is subsequently found to be inaccurate, misleading or incomplete, or due to the acts or omissions of any person other than ourselves. LM Environmental Consulting shall not be liable for any direct, incidental, special or consequential damages for loss of profit, revenue, data or use incurred by the Client or any third party, whether in contract or delict, regardless whether the Client or the other party has been advised of the possibility of such damages.

Copyright Warning: Unless otherwise noted, the copyright in all text and other matter (including the manner of presentation) is the exclusive property of LM Environmental Consulting and/or Dr Maartens. It is an offence to reproduce and/or use, without written consent, any substance, matter, technical procedure and/or technique or part thereof contained in this document.

TABLE OF CONTENTS

1	Intro	oduction	5
	1.1	Background	
	1.2 1.3	Activities Terms of Reference	
	1.4	Environmental Assessment Practitioner	
2	Envi	ironmental Management Plan: Implementation and Compliance	10
	2.1	Introduction	10
	2.2	Compliance: Environmental Management Plan	
	2.3	Compliance: Conditions attached to the ECC for Sand Mining	
3	Con	clusions and Recommendations	31
4	Refe	erences	32
5	Ann	exure A	33
LIST	OF 1	TABLES	
		ompliance by Namibia Construction (Pty) Ltd's with the Environmental Management Plan sand mining, exploration and quarrying for construction materials) on the Remainder of Pol	
		nhuk No. 30, Khomas Region, Namibia	
LIST	OF F	FIGURES	
		Map showing the location of the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Source: Linear Design and Mapping, September 2016)	
Figur quarr	e 2: ying a	Map showing the location of Namibia Construction's sand mining, exploration and activities on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, inear Design and Mapping, September 2016)	possible Namibia
Figur	e 3: F	Pictures showing some of the material stockpiled at the laydown area (Source: L. Maar 2020)	rtens, 25
Rema	ainder	Updated" map showing the location of Namibia Construction's proposed "new" borrow pir of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (<i>Source:Miss Maike alist, February 2020</i>)	Prickett,
Figur with t Figur	e 5: P he Ari e 6: F	Pictures showing the proposed "new" borrow pit-area: a) in the foreground and looking eas is Mountains in the background (<i>Source: L. Maartens, 25 February 2020</i>)	it; and b) 8 irea had
		O millimetres of rain since December 2019) (Source: L. Maartens, 25 February 2020)	16
ACR	ONY	MS AND GLOSSARY	

The following is a list of the abbreviations, acronyms, technical terms, and definitions used in this Report:

ADT Articulated Dump Truck

AIDS Acquired Immunodeficiency Syndrome

CIF Construction Industries Federation of Namibia

CoW City of Windhoek

(Malaysian) Department of Irrigation and Drainage Environmental Assessment Practitioner DID

EAP

EAPAN Environmental Assessment Professionals of Namibia

ECC Environmental Clearance Certificate
EIA Environmental Impact Assessment
EMA Environmental Management Act
EMP Environmental Management Plan

GN Government Notice

GRN Government of the Republic of Namibia

HIV Human Immunodeficiency Virus I&APs Interested and Affected Parties

IEMA Institute of Environmental Management and Assessment

IFC International Finance Corporation
MANWU Metal Allied and Namibia Workers Union
MAWF Ministry of Agriculture, Water and Forestry
MET Ministry of Environment and Tourism
MFMR Ministry of Fisheries and Marine Resources

MSDS Material Safety Data Sheet
NC Namibia Construction (Pty) Ltd
NCE Namibia Chamber of Environment

PDAC Prospectors and Developers Association of Canada

PM Particulate Matter

PPE Personal Protective Equipment

SA South Africa

SHE Safety, Health, Environment STIs Sexually Transmitted Infections

UK United Kingdom
UNAM University of Namibia
VOC Volatile Organic Compound

cm centimetre kg kilogramme km kilometre

km/h kilometre per hour

I litre
m metre
mm millimetre
m³ cubic metre

m³/day cubic metres per day

1 Introduction

1.1 Background

Namibia Construction (Pty) Ltd (hereinafter referred to as Namibia Construction or NC) is a wholly-owned Namibian Company that was founded in 1949. At the time, the Company was called HH Schulz. In 1977, the name was changed (from HH Schulz) to Namibia Construction (Pty) Ltd.

Namibia Construction provides services in civil engineering, building construction, crushing, and the supply of ready mix concrete. The Company is qualified and experienced to perform the following activities: earth works; layer works; surfacing works; concrete works; building of bridges; drainage and culverts; and road signage and markings (see http://www.namibia-construction.com/).

In 2016, Namibia Construction proposed to mine sand from the Usip Riverbed and to quarry for construction materials (stone/gravel) on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (see Figures 1 and 2).




Figure 1: Map showing the location of the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (*Source: Linear Design and Mapping, September 2016*).

In line with the Commencement of the Environmental Management Act (EMA), 2007 (Act No. 7 of 2007) (06 February 2012; Government Notice (GN) No. 28), the Listed Activities that may not be undertaken without an Environmental Clearance Certificate (ECC) (GN No. 29), and the Environmental Impact Assessment (EIA) Regulations (GN No. 30) (Government of the Republic of Namibia (GRN), 2012), Namibia Construction applied to the Environmental Commissioner for an ECC on 04 October 2016.

An Environmental Scoping and Management Plan Report for the Mining of Sand and Quarrying for Construction Materials by Namibia Construction (Pty) Ltd on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (Maartens, 2017) was submitted to the Office of the Environmental

Commissioner on 31 January 2017. An ECC, with conditions attached to it, was received from the Office of the Environmental Commissioner on 06 June 2017 (see Annexure A).

1.2 Activities

At the time, Namibia Construction prepared a laydown area (see Figure 2) where sand, gravel, etc. were to be stockpiled; the area, 80 by 100 metres (m) in size, was fenced (to keep cattle and game out) and surrounded by a strip of open space that served as a firebreak.

A gravel (haul) road (~1.3 kilometre (km) in length) was constructed between the laydown area and the Usip Riverbed (where sand mining was taking place). Drainage pipes were installed in the tributaries next to the road so that the road does not wash away during the rainy season. The material to construct the road (~4,500 cubic metres (m³)) was obtained from the Wearing Course Borrow Pit (see Figure 2).




Figure 2: Map showing the location of Namibia Construction's sand mining, exploration and possible quarrying activities on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (Source: Linear Design and Mapping, September 2016).

Between 10,000 and 12,000 m³ of sand was mined from the Usip Riverbed by means of a 324 Excavator. Two Articulated Dump Trucks (ADTs) hauled the sand from the riverbed to the laydown area and at the laydown area, the sand was stockpiled and then transported by means of horse, trailer, and 10 m³ tipper trucks to NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek. It was anticipated that ~60,000 m³ of sand will be mined from a 1.6 km strip (~1.5 m deep). However, the clay content of the sand was found to be too high, and the sand mining was put on hold.

NC also proposed to do exploration (i.e. diamond drilling: three boreholes up to 15 m depth) to determine the feasibility of opening up another borrow pit (see Figure 2: Proposed Quarry Area).

In 2017, it was unlikely that any material (i.e. gravel for road construction) will be sourced from the Proposed Borrow Pit (see Figure 2); a small amount of gravel (~1,000 m³), however, was taken from this borrow pit.

Water was obtained from a borehole ~4 km to the south of the "laydown area" (this borehole also supplies the Primary School at Aris). Around 2 m³ of water per week was needed (mainly for use by the security guard that stayed at the laydown area); water for human consumption was stored in a closed, 5,000 litre (I) tank. There is a water meter and Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and Social Development) was compensated by NC for the water used.

Water for dust suppression (~30 cubic metres per day (m³/day)) was obtained from Kunene Building Supplies; a water bowser transported and delivered the water to NC's site on an *ad hoc* basis.

Namibia Construction proposed the use of chemical toilets at the Remainder of Portion 9 of Farm Krumhuk No. 30; Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and Social Development), however, preferred that NC's staff make use of a pit latrine(s) (longdrop). The pit latrine was treated with a chemical toilet cleaner (Taurus-range) on a two-weekly basis.

All solid waste was removed from the site and disposed of at NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill).

As very little sand was mined from the Usip Riverbed, no exploration activities took place, and only a small amount of material was sourced from the Proposed Borrow Pit, all infrastructure (including the fence) at the laydown area has since been removed. Some material is still stockpiled in the area (see Figure 3).



Figure 3: Pictures showing some of the material stockpiled at the laydown area (Source: L. Maartens, 25 February 2020).

Namibia Construction will resume their activities in the area, and is also looking at opening up another borrow pit to source gravel for road construction. The proposed area is located north north-east of the laydown area, and to the west of the farm road (track) and TransNamib Holdings Ltd's servitude (see Figures 4 and 5). The area is not considered ecologically sensitive (see Figure 5).




Figure 4: "Updated" map showing the location of Namibia Construction's proposed "new" borrow pit, on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia (Source:Miss Maike Prickett, GIS-Specialist, February 2020).



Figure 5: Pictures showing the proposed "new" borrow pit-area: a) in the foreground and looking east; and b) with the Aris Mountains in the background (*Source: L. Maartens, 25 February 2020*).

1.3 Terms of Reference

LM Environmental Consulting was appointed by Namibia Construction (Pty) Ltd in February 2020 to prepare a report, illustrating the implementation of and compliance with the Environmental Management Plan (EMP), in aid of the application for the renewal of the ECC for the mining of sand and quarrying for construction materials on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia.

1.4 Environmental Assessment Practitioner

The author of this Report is Dr Lima Maartens who has more than 27 years' experience in natural resource management (she gained her doctorate (Ph.D.) in Fisheries Science from Rhodes University, South Africa (SA) while working for the Namibian Ministry of Fisheries and Marine Resources (MFMR) in 2000, lecturing (University of Namibia (UNAM)), environmental science and management (De Beers Marine Namibia and the Canadian Forsys Metals Corp), and consulting). Dr Maartens is registered as a Lead Practitioner and Reviewer with the Environmental Assessment Professionals of Namibia (EAPAN) (she served on the Executive Committee during 2016/17), an Associate Member and Environmental Auditor with the Institute of Environmental Management and Assessment (IEMA) in the United Kingdom (UK), an Associate Member of the Namibia Chamber of Environment (NCE), and a Member of the Namibia Scientific Society. LM Environmental Consulting was established by Dr Maartens in October 2009.

2 Environmental Management Plan: Implementation and Compliance

2.1 Introduction

As part of the EMP performance review, the following actions were carried out:

- A meeting was held with Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd on 19 February 2020; and
- A site visit was subsequently undertaken, together with Mr Luther du Plessis, Civil Division, Namibia Construction (Pty) Ltd and Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and Social Development), to the area on 25 February 2020.

2.2 Compliance: Environmental Management Plan

In order to illustrate compliance with the EMP (see Table 1), the following colour codes were applied:

Compliance/Completed	
In Progress/Ongoing	
Non-compliance	
Not (Currently) Applicable	
Changes made to existing EMP	

Note that all activities in the area have been put on hold (after small amounts of sand and fill was mined and sourced from the Usip Riverbed and Proposed Borrow Pit, respectively). Compliance with the EMP will thus mostly be, either "ongoing" (taking into account the ongoing activities / operation of Namibia Construction), or "Not Applicable (N/A) (Currently)".

The EMP (see Maartens, 2017; also see International Finance Corporation (IFC), 2007a, b; (Malaysian) Department of Irrigation and Drainage (DID), 2009; Prospectors and Developers Association of Canada (PDAC), 2009) is not a static document and the document should be updated as Namibia Construction's activities progresses.

Table 1: Compliance by Namibia Construction (Pty) Ltd's with the Environmental Management Plan for the activities (sand mining, exploration and quarrying for construction materials) on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia.

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
Social and Environmental Performa			
Management and Monitoring	Social and Environmental Performance	Adhere to all Namibian Legislation, including Best Practice Guidelines.	Ongoing (Company)
		Ensure that all aspects related to the	Ongoing; Namibia Construction (Pty) Ltd (NC)
		Environmental Management Plan (EMP) are implemented.	also has a Baseline Environmental Management Plan in place.
		Ensure that the Rehabilitation Plan is	N/A (Currently)
		implemented (see Maartens, 2017:	Tw/ (Carronay)
		Annexure G – Kolberg, 2016b).	
Consultation and Disclosure	Social and Environmental	Maintain open and direct lines of	Ongoing
	Performance	communication with the Authorities and	
		Interested and Affected Parties (I&APs)	
		(e.g. Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and	
		Social Development), the Ministry of	
		Environment and Tourism (MET), the	
		Ministry of Agriculture, Water and Forestry	
		(MAWF), and the City of Windhoek (CoW)	
		with regards to environmental matters.	
		Consult with I&APs throughout the project	
		process and adequately incorporate I&APs'	
<u> </u>	0	concerns.	O : (N/A /O : #)
Grievance Mechanism	Social and Environmental Performance	Implement a grievance mechanism for receiving and resolving any concerns and	Ongoing / N/A (Currently)
	Fellolliance	grievances related to the project's social	
		and environmental performance throughout	
		the project life cycle.	
		Inform all I&APs about the mechanism.	
		Address concerns promptly and	
		transparently and in a culturally appropriate	
		manner.	
		Keep a register of all concerns/issues	
		received from I&APs, as well as the measures taken to address these.	
Training, including awareness and	Social and Environmental	Train employees and contractors in matters	Ongoing (as part of e.g. the toolbox talks) (Mr
inductions	Performance	related to the project's social and	Wilfried Schmidt, Contract Manager, Civil
		environmental performance and Namibia's	Division, Namibia Construction (Pty) Ltd, pers.
		regulatory requirements.	comm.).
		Ensure adequate environmental awareness	
		training for all senior site personnel.	
		Give environmental induction presentations	

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		to all site personnel.	
Employment and procurement opportunities	Social and Environmental Performance	Source contracting companies/service providers/experts/workers based on merit and expertise giving preference to local contractors/service providers/experts/workers on condition that the local contractors/service providers/experts/workers have the required experience and expertise.	N/A
		Consider utilising local labour for unskilled work and to then provide training to workers in order to perform semi-skilled work; this should be done under the supervision of managers/specialists to ensure maximum local beneficiation.	N/A
		Ensure that contractors/service providers/experts adhere to the Namibian Labour, Social Security, Health and Safety, and Affirmative Action laws.	N/A
		Contracts to stipulate that all contractors/service providers have an HIV/AIDS Policy and Programme in place.	N/A
		Source maximally from local resources to ensure maximum economic beneficiation of local businesses in terms of new business sales.	Ongoing (Company)
Labour and Working Conditions	Social and Environmental Performance	Establish, maintain and improve the worker-management relationship. Base the employment relationship on equal opportunity and fair treatment and no discrimination to be allowed. Comply with Namibia's labour and	NC is a member of the Construction Industries Federation of Namibia (CIF) and the Metal Allied and Namibia Workers Union (MANWU). Labour disputes are handled (externally) by Labour Dynamics cc.
		employment laws. Promote safe and healthy working conditions and the protection and promotion of worker health.	The following Company Policies are in place: Health and Safety; Environmental; HIV/AIDS; General Health and Safety; Alcohol and Drug Zero Tolerance; Fire Arm; Sexual Harassment;
		Document and communicate the Working Conditions and Terms of Employment. Respect Collective Agreements and the right of workers to organize and bargain collectively. Implement a Grievance Mechanism.	Smoking; Information Technology; Cell Phone; Life Threatening Disease; Personal Protective Equipment; and Quality.
Occupational and Community Health, Safety and Security	Social and Environmental Performance	Adhere to all Namibia's Health and Safety Regulations (Labour Act, 1992: Regulations	NC is a member of the CIF and the MANWU.

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		Relating to the Health and Safety of Employees at Work).	
		Ensure that an HIV/AIDS Policy and Programme and Health and Safety Plan are in place.	Health and Safety, HIV/AIDS, and General Health and Safety Policies are in place.
		A SHE (Safety, Health, Environment) Representative to be appointed once the staff complement reaches 20.	OSH Representatives (Shop Stewards) only; environmental matters are addressed as part of e.g. the toolbox talks (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Occupational Health and Safety Training to be provided to all employees.	The following training are provided to NC staff: OSH Representative (Health and Safety) and First Aid Level A (at OSH-Med International); and Advance Rigging "Refresh" and 7 Ton Tower Crane Refresh (at H.J.L. Trading CC). NC also has a Health, Safety, & Environment Safe Operating Procedure Fire Prevention in place.
		Ensure that qualified first aid can be provided at all times.	Sick or injured staff is transported to the Roman Catholic Hospital in Windhoek (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Comply with all safety regulations re. electricity supply (if applicable).	Ongoing (Company)
		Ensure that employees are trained in the use of appropriate fire fighting equipment and ensure that such equipment is on hand at all times.	NC has a Health, Safety, & Environment Safe Operating Procedure Fire Prevention in place.
		Provide and ensure the active use of Personal Protective Equipment (PPE) (e.g. protective glasses and dust masks in dusty working conditions, overalls, gloves, safety shoes and hard hats).	Ongoing (Company) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Supply potable water for human consumption and other domestic uses; conduct chemical testing of water samples; drinking-water quality to be in accordance with the MAWF's Water Quality Guidelines and Standards for Potable Water (2008)*.	N/A (currently); at the time, around 2 cubic metres (m³) of water per week was needed (mainly for use by the security guard that stayed at the laydown area).
		Make suitable arrangements, as far as practicable, for the maintenance of health, the prevention and overcoming of outbreaks of disease and of adequate first aid services.	Ongoing (Company)
		Prevent communicable disease (e.g.	Ongoing (Company)

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
Ларви	impact	Sexually Transmitted Infections (STIs) such as HIV transmission): provide surveillance and active screening and treatment of employees; prevent illness among employees (through health awareness and education initiatives); ensure ready access to medical treatment, confidentiality and appropriate care, particularly with respect to migrant workers; and promote immunization. Ensure that security arrangements are in	At the time, NC appointed a security guard that
		place.	stayed in an old caravan at the laydown area (Maartens, 2017).
		Notice or information boards relating public and occupational health and safety hazards and emergency contact details should be put up at the laydown area.	N/A (Currently)
		Transport safety: all vehicles/trucks moving on the (internal) roads should not exceed 30 kilometres per hour (km/h); vehicles/trucks moving on the B1 to adhere to the speed limits of Namibia (and NC's Company Policy if applicable).	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Enforce a strict ban on the recruitment of workers at the entrances to the laydown area and on visitors gaining entry to the workers on site.	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Restrict construction/mining/quarrying activities to demarcated areas; all other areas will be regarded as "no go" zones in order to minimise the impact on the surrounding land/properties.	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		terials on the Remainder of Portion 9 of Farr	
Exploration Activities (Diamond Drilling), Construction of Laydown Area, Borrow Pits and Roads, Sand Mining and Quarrying	Clearing of vegetation / negative impact on floral species	Avoid the sensitive areas immediately adjacent to the development areas (areas with white quartz pebbles and the granite cliffs); keep a buffer zone of at least 10 metres (m) at the base of the cliffs, do not expand the Wearing Course Borrow Pit, and do not store any material in the area (to the north of the Wearing Course Borrow Pit).	N/A (Currently)
		Restrict construction/mining/quarrying activities to demarcated areas; all other	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt,

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		areas will be regarded as "no go" zones in	Contract Manager, Civil Division, Namibia
		order to minimise the impact on the flora.	Construction (Pty) Ltd, pers. comm.).
		Create awareness among staff and	N/A (Currently)
		contractors about the importance of the	
		vegetation in this area.	
		Avoid the removal of and/or damage to any	N/A (Currently)
		protected flora species as far as feasible. A	
		permit is required prior to the picking,	
		cutting/chopping/picking off, taking,	
		gathering, uprooting, damaging or	
		destroying, or transporting any protected	
		tree and/or plant.	N/A /O II NO
		Avoid off-road driving in the area.	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Monitor dust or Particulate Matter (PM) pollution and implement dust control/suppression methods (should it be required).	N/A (Currently); Compliant (when NC was operational in the area). Water for dust suppression (~30 cubic metres per day (m³/day)) was obtained from Kunene Building Supplies; a water bowser transported and delivered the water to NC's site on an <i>ad hoc</i> basis (Mr Wilfried Schmidt, Contract Manager, Civil Division,
		Implement the Rehabilitation Plan (see Maartens, 2017: Annexure G – Kolberg, 2016b).	Namibia Construction (Pty) Ltd, pers. comm.). N/A (Currently)
		Avoid removing vegetation adjacent to the Usip River. Leave a buffer zone of undisturbed vegetation at least 10 m wide on either side of the River (i.e. the excavation of sand should be at least 10 m away from the Usip River bank). Vertical slopes resulting from excavations shall not be higher that one (1) m; ideally, the zone must be sloped from the mined area to the trees and not be a vertical, 90 degree drop (in order to reduce erosion of soil away from the roots of the trees on the Usip River bank).	N/A (Currently); Compliant (when NC was operational in the area; also see Figure 6) (Mr Luther du Plessis, Civil Division, Namibia Construction (Pty) Ltd and Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and Social Development), pers. comm.).
		Create weirs to slow flow of water on slopes (and to avoid erosion).	N/A (Currently)
		Implement strip mining in river bed (to increase sedimentation and decrease	N/A (Currently)

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		erosion along the river bank).	
		Avoid blocking water flow patterns by	N/A (Currently); Compliant (when NC was
		infrastructure (e.g. use pipes under roads	operational in the area) (Mr Wilfried Schmidt,
		so that water can flow across) and avoid	Contract Manager, Civil Division, Namibia
		putting permanent structures in	Construction (Pty) Ltd, pers. comm.).
		watercourses.	



Figure 6: Pictures showing the eroded banks due to the recent flowing of the Usip River (the area had around 200 millimetres of rain since December 2019) (Source: L. Maartens, 25 February 2020).

Possible loss of the seed bank in the topsoil	Any decaying vegetation, overlying the soil layer, should be removed first and	N/A (Currently)
	stockpiled.	
	The upper layer of soil (10 - 20 centimetres (cm)), where alluvial, to be stripped and	
	allow for proper aeration). Install drainage	
	erosion and cover it to protect it from (wind) erosion.	
	Any excavated subsoil and rock also to be stockpiled for backfilling.	
Disturbance of fauna and flora and habitat alteration	Avoid the removal of any protected flora species as far as feasible. A permit is required prior to the picking, cutting/chopping/picking off, taking, gathering, uprooting, damaging or	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		The upper layer of soil (10 - 20 centimetres (cm)), where alluvial, to be stripped and stockpiled separately (1 - 2 m high piles to allow for proper aeration). Install drainage to protect the topsoil pile from (water) erosion and cover it to protect it from (wind) erosion. Any excavated subsoil and rock also to be stockpiled for backfilling. Disturbance of fauna and flora and habitat alteration Avoid the removal of any protected flora species as far as feasible. A permit is required prior to the picking, cutting/chopping/picking off, taking,

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
АБРЕСТ	Impact	tree and/or plant. No open fires are allowed to be made on Farm Krumhuk and no wood or any other items are allowed to be collected and removed from Farm Krumhuk (as per Memorandum of Agreement (MoA)). No animals may be kept in the area (as per MoA). Ensure the availability of firefighting equipment (e.g. fire beaters, spades, extinguishers, etc.). Do not introduce non-indigenous/invasive alien plant species. No wild animal may be injured, fed, trapped or harmed in any way. Implement a policy of "no kill" with regards to fauna (e.g. poaching for meat (snares); the collection of veld foods (e.g. tortoises); the capture/killing of birds; the killing of snakes, etc.). Implement a suitable and appropriate refuse removal policy (littering could result in certain animals becoming accustomed to humans and the associated activity and result in typical problem animal scenarios).	N/A (Currently); Compliant (when NC was operational in the area). Solid waste was removed from the site and disposed of at NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017).
		Avoid off-road and unnecessary nocturnal driving in the area (as it could result in the destruction of slow moving fauna, i.e. various reptiles and other nocturnal species). Implement and maintain (internal) track discipline with maximum speed limits (e.g. 30 km/h) (this would result in fewer faunal road mortalities and associated dust pollution problems). Teach drivers to use three point turns (vs full circle turns), or restrict turning to designated areas. Restrict construction/mining/quarrying activities to demarcated areas; all other areas will be regarded as "no go" zones in order to minimise the impact on the	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		surrounding land. No trespassing on adjoining properties is allowed and no game/vegetation is to be interfered with.	
Exploration Activities (Diamond Drilling), Construction of Borrow Pits and Roads, Sand Mining and Quarrying	Loss of or damage to archaeological material	All staff to be made aware of the provisions of the National Heritage Act 27 of 2004 with regard to the protection of all archaeological sites and the need to report any new finds. Carefully examine the area before any site preparation/excavation is undertaken. Implement the Chance Finds Procedure (see Maartens, 2017: Annexure D): should a possible or suspected site be discovered (e.g. a grave), immediately stop work, cordon the area off and photograph the area/site; immediately inform the project manager/supervisor, and contact Dr Kinahan, the National Heritage Council of Namibia, and the Police in Windhoek. Under no circumstances are archaeological and/or cultural heritage sites to be disturbed or any relics to be removed from such a site.	N/A (Currently)
Exploration Activities (Diamond Drilling), Construction of Borrow Pits and Roads, Sand Mining and Quarrying	Pollution of biophysical environment (air, soil and water)	No open fires are allowed to be made on Farm Krumhuk (as per MoA). Cooking appliances (e.g. gas stoves) are to be properly maintained and ventilated. Pit latrines to be provided by NC and used by the staff.	N/A (Currently); Compliant (when NC was operational in the area) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.). N/A (Currently). At the time of operation, there was one pit latrine; 20 kilogrammes (kg) of builder's lime was added to the pit latrine at the start and the pit latrine was treated with a chemical toilet cleaner (Taurus-range) on a two-weekly basis afterwards (Maartens, 2017).
		Sanitary wastewater to be released into a French drain system. Use bio-degradable detergents on site. Vehicle maintenance/servicing/washing not to be allowed anywhere on site. Fuel tanks (portable), gas cylinders and chemicals (if relevant) are to be properly stored and transported. All diesel generators on site (if relevant) to	N/A (Currently) N/A (Currently) N/A (Currently). At the time of operation, a service truck delivered fuel to the area on a daily basis (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.). N/A

Collected and disposed of at least once a week. Windhoek landfill) (Maartens, 2017).	Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
installed and maintained. Immediately report and clean up any accidental hydrocarbon spill: Sunsorb, Drizit, Peatsorb can be used to clean up small spills; in case of larger spills, the spill together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
Immediately report and clean up any accidental hydrocarbon spill: Sunsorb, Drizit, Peatsorb can be used to clean up small spills; in case of larger spills, the spill together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) — waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				N/A (Currently)
accidental hydrocarbon spill: Sunsorb, Drizit, Peatsorb can be used to clean up small spills; in case of larger spills, the spill together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non- hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Exploration Activities (Diamond Drilling, including Rigs, Vehicles, a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. N/A (Currently); Compliant (when NC was operational in the area). Solid waste was removed from the site and disposed of at NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017). N/A (Currently) Pollution of biophysical environment (soil and fluids/additives.				
Drizit, Peatsorb can be used to clean up small spills; in case of larger spills, the spill together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and nonhazardous) management practices (as per Waste Management Plan) — waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				N/A (Currently)
small spills; in case of larger spills, the spill together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and nonhazardous) management practices (as per Waste Management Plan) — waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the minedout quarry). Pollution of biophysical prilling, including Rigs, Vehicles,				
together with the polluted soil should be removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
removed and disposed of at e.g. a biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and nonhazardous) management practices (as per Waste Management Plan) — waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Enturn overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the minedout quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
biological remediation site; ensure the availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
availability of absorbent pads and/or spill kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
kits and ensure that personnel are trained in their use. Enforce proper waste (hazardous and non-hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, N/A (Currently); Compliant (when NC was operational in the area). Solid waste was removed from the site and disposed of at NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017). N/A (Currently) N/A (Currently) N/A (Currently) N/A (Currently)				
their use. Enforce proper waste (hazardous and nonhazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the minedout quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles,				
Enforce proper waste (hazardous and nonhazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, Pollution of biophysical environment (soil and				
hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, hazardous) management practices (as per Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017). N/A (Currently) N/A (Currently)				N/A (Currently): Compliant (when NC was
Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, Waste Management Plan) – waste and litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at INC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017). N/A (Currently) N/A (Currently)				
litter to be disposed of in scavenger and weatherproof bins and the refuse to be collected and disposed of at least once a week. Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill) (Maartens, 2017). N/A (Currently) N/A (Currently)				
Collected and disposed of at least once a week. Windhoek landfill) (Maartens, 2017).				
week. 2017). Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and length of the prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Use biodegradable and non-toxic drill fluids/additives.				Northern Industrial Area, Windhoek (for ultimate
Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and leaves of the mined-out quarry). Return overburden to mined-out quarry (to prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). N/A (Currently) N/A (Currently)			collected and disposed of at least once a	
prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and prevent the accumulation of exposed, stagnant water) and rehabilitate (the mined-out quarry). Use biodegradable and non-toxic drill fluids/additives.				
stagnant water) and rehabilitate (the mined- out quarry). Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and stagnant water) and rehabilitate (the mined- out quarry). Use biodegradable and non-toxic drill fluids/additives.				N/A (Currently)
Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and environment (soil an				
Exploration Activities (Diamond Drilling, including Rigs, Vehicles, environment (soil and Pollution of biophysical environment (soil and Pollution of biophysical fluids/additives.				
Drilling, including Rigs, Vehicles, environment (soil and fluids/additives.	Exploration Activities (Diamond	Pollution of biophysical		N/A (Currently)
			_	TWA (Currently)
Generators) groundwater) All diesel generators on site to be placed on		groundwater)	All diesel generators on site to be placed on	
a tarpaulin sail.	Constant of	g.caa.a.,	,	
Oil traps to be installed in appropriate				
places to collect potential toxic materials.				
Immediately report and clean up any				
accidental hydrocarbon spill: Sunsorb,				
Drizit, Peatsorb can be used to clean up				
small spills; in case of larger spills, the spill				
together with the polluted soil should be				
removed and disposed of at e.g. a				
biological remediation site.				
Ensure the availability of absorbent pads				
and/or spill kits and ensure that personnel are trained in their use.				
(Backfill or) seal all drill holes with a steel or				
uPVC casing equipped with a secure cap				
(to prevent groundwater contamination from				
taking place through the drill holes).				

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		Drill cuttings not to be used for backfilling;	
		use clean sand or clay where possible.	
		Drill holes not to be used as pit latrines	
		and/or for the disposal of waste.	
Exploration Activities (Diamond	Soil erosion	Sediment mobilization and transport:	N/A (Currently)
Drilling), Construction of Laydown		reduce or prevent soil erosion (schedule	
Area, Borrow Pits and Roads, Sand		activities to avoid heavy rainfall periods;	
Mining and Quarrying		contour and minimise length and steepness	
		of slopes; mulching to stabilize exposed	
		areas; re-vegetate areas promptly (if	
		feasible); and design channels and ditches for post-construction flow). Note that the	
		area(s) towards and adjacent to the	
		drainage line(s) are easily eroded and	
		further development may exacerbate this	
		problem.	
		problem.	
		Road design: limit access road gradients to	
		reduce run-off induced erosion; provide	
		adequate road drainage based on road	
		width, surface material, compaction and	
		maintenance.	
		Structural (slope) stability: provide effective	
		short-term measures for slope stabilization,	
		sediment and subsidence control until long-	
		term measures (during operations) can be	
		implemented; provide adequate drainage	
		systems to minimise and control infiltration.	
Traffic, presence and movement of	Air quality (dust or Particulate	Minimise dust generation from vehicles on	N/A (Currently); Compliant (when NC was
machinery	Matter (PM) pollution)	the roads; all vehicles/trucks moving on the	operational in the area) (Mr Wilfried Schmidt,
		gravel roads should not exceed 60 km/h; all	Contract Manager, Civil Division, Namibia
		vehicles, trucks moving within Farm Krumhuk should not exceed 30 km/h.	Construction (Pty) Ltd, pers. comm.).
		Minimise the area in which the movement of vehicles will take place to reduce the effects	
		of dust pollution.	
		Avoid the excavation, handling and	
		transport of erodible materials under high	
		wind conditions or when a visible dust	
		plume is present.	
		Maintain the road surface to preserve	
		surface characteristics (e.g. texture and	
		roughness).	

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		Use dust control/suppression methods (if needed), such as applying water or nontoxic chemicals to minimise dust (oil and oil by-products is not a recommended measure to control road dust).	N/A (Currently); Compliant (when NC was operational in the area). Water for dust suppression (~30 m³/day) was obtained from Kunene Building Supplies; a water bowser transported and delivered the water to NC's site on an <i>ad hoc</i> basis (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Traffic, presence and movement of machinery (exhaust from diesel engines)	Air quality & Occupational and Community Health and Safety	Implement manufacturer recommended engine maintenance programmes (to control vehicle emissions: carbon monoxide (CO), nitrogen oxides (NO _x), sulphur dioxide (SO ₂), Particulate Matter (PM) and Volatile Organic Compounds (VOCs)).	Ongoing (Company) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Traffic, movement of machinery	Occupational and Community Safety	Adopt best transport safety practices by implementing the following measures: emphasize safety aspects among drivers; improve driving skills and require licensing of drivers; adopt limits for trip duration; avoid dangerous routes and times of day; and use speed control devices. Regularly maintain vehicles and use manufacturer approved parts. Use locally sourced materials (where possible) to minimise transport distances. Employ safe traffic control measures, including the use of traffic and safety warning signs and flag persons to warn of dangerous conditions.	Ongoing (Company) All trucks are fitted with vehicle tracking devices (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Sand Mining in the Usip Riverbed			
Sand Mining	Changes to river morphology, habitat alteration, erosion	The excavation of sand to be at least 200 m from any developed areas/plots in the flood plains and on the river banks. Do not pollute, block or deflect the normal underground flow of water in the Usip River, as well as the periodic visible run-off and floods. Base the (sand) mining volume on the measured annual replenishment (of sand). Establish an absolute elevation below which no extraction may occur (the "redline"). The MAWF requires that excavation shall under no circumstances expose the ground water table and shall have slopes not higher than	N/A (Currently)

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
·	·	4 m. Vertical slopes resulting from	·
		excavations shall not be higher than 1 m.	
		Limit in-stream mining methods to bar	
		skimming.	
		Extract sand from the downstream portion	
		of the bar.	
		Concentrate in-stream mining activities to	
		minimise the area of disturbance.	
		Review, on an annual basis, the cumulative	
		effects of sand extraction.	
		Maintain river channel flood discharge	
		capacity (flood capacity in the river to be	
		maintained in areas where there are	
		significant flood hazards to existing	
		structures or infrastructure).	
		Establish a long-term monitoring	
		programme (to monitor changes in bed	
		elevation and channel morphology, and	
		riparian habitat upstream and downstream	
		of the in-stream mining site).	
		Minimise activities that release fine	
		sediment to the river (i.e. no washing,	
		crushing, screening, stockpiling, or plant operations to occur at or below the stream's	
		"average high water elevation").	
		Retain the riparian buffer at the edge of the	
		water and against the river bank (where	
		feasible; the riparian zone is necessary to	
		the integrity of the ecosystem providing	
		habitat for invertebrates, birds and other	
		wildlife).	
		Limit in-stream mining to take place during	
		the dry season only.	
		Follow the following setbacks and mining	
		envelope levels (for in-steam mining): the	
		excavation must be setback for a minimum	
		distance of 10 m from the main channel	
		bank toward the flow channel; stockpiles (if	
		applicable and where feasible) to be located	
		30 m to the right or left of the main channel	
		bank; the minimum depth of the excavation	
		or redline to be at one (1) m deposition	
		above natural thalweg elevation; a	
		maximum allowable mining depth of 1.5 m.	

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		terials on the Remainder of Portion 9 of Farr	
Energy Management	Resource use (e.g. coal) / depletion of natural resources	Promote the sustainable use of energy (that will result in the reduction of use and cost reductions) (e.g. energy efficient light sources).	N/A (Currently)
		Raise awareness amongst the staff and contractors/service providers (to save energy).	N/A
Water Management	Resource use / depletion of natural resources	Ensure prudent use of water in all activities. Implement a water conservation program, promoting the continuous reduction in water consumption; treatment and disposal costs commensurate with the magnitude and cost of water use.	Ongoing (Company) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		Water storage tanks to be insect and animal-proof and to be covered to reduce evaporation.	N/A (Currently); Compliant (when NC was operational in the area). The 5,000 litre (I) water tank was covered (Maartens, 2017).
Sand Mining, Exploration and Poss	ible Quarrying for Construction Ma	Record monthly water meter readings (to demonstrate low water consumption); should consumption exceed 20 cubic meters per month (m³/month) then the reason(s) therefore should be recorded. terials on the Remainder of Portion 9 of Farm	N/A (Currently) n Krumhuk No. 30: Hazardous Materials
Management Hazardous materials management	Social and Environmental	Establish hazardous materials management	N/A (Currently)
Ç	Performance	priorities (based on hazard analysis of risky operations). Avoid, or minimise the use of hazardous materials.	•
		Prevent uncontrolled releases of hazardous materials to the environment or uncontrolled reactions that may result in fire or explosion.	
		Implement management controls (procedures, inspections and training, communication and drills) to address residual risks.	
Hazardous materials management	Pollution of biophysical environment (soil and water)	Implement prevention and control measures for the use, handling and storage of hazardous materials: Materials transfer (if relevant): regularly inspect, maintain and repair fittings/pipes/hoses; make use of drip trays/other drip containment measures at	Ongoing (Company) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		connection/possible overflow points;	
		Overfill protection if relevant): use trained	
		filling operators; install gauges on tanks to	
		measure the volume inside; make use of	
		dripless hose connections (vehicle tanks)	
		and fixed connections (storage tanks); use	
		a catch basin/drip tray around the fill pipe to	
		collect spills;	
		Reaction, fire, and explosion prevention:	
		hazardous materials to be stored in marked	
		containers and separate (from non-	
		hazardous materials); incompatible	
		hazardous materials (acids, bases,	
		flammables, oxidizers, reactive chemicals)	
		to be stored in separate areas and with	
		containment facilities separating material	
		storage; smoking or working with open	
		flames not to be permitted in the presence	
		of these substances; limit access to	
		hazardous waste storage areas and clearly label and demarcate the area; conduct	
		regular inspections of the areas and	
		document the findings; prepare and	
		implement spill response and emergency	
		plans; train employees in the use of	
		appropriate fire fighting equipment and	
		ensure that such equipment is on hand at	
		all times.	
		Train workers on the correct transfer and	
		handling of fuels and chemicals (if relevant)	
		and the response to spills.	
		Immediately report and clean up any	
		accidental hydrocarbon spill: Sunsorb,	
		Drizit, Peatsorb can be used to clean up	
		small spills; in case of larger spills, the spill	
		together with the polluted soil should be	
		removed and disposed of at e.g. a	
		biological remediation site.	
Hazardous materials management	Occupational Health and Safety	Implement hazard communication and	Ongoing (Company). The only hazardous
		training programmes (including information	materials used, is fuel (Mr Wilfried Schmidt,
		on Material Safety Data Sheets (MSDS)) to	Contract Manager, Civil Division, Namibia
		make employees aware of workplace	Construction (Pty) Ltd, pers. comm.).
		chemical hazards and how to respond to	, , , , ,
		these.	
		Provide and ensure the active use of PPE.	Ongoing (Company) (Mr Wilfried Schmidt,

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
			Contract Manager, Civil Division, Namibia
			Construction (Pty) Ltd, pers. comm.).
		terials on the Remainder of Portion 9 of Farn	
Waste management: non-hazardous	Pollution of biophysical	Ensure that a Waste Management Plan is in	Ongoing (Company). The City of Windhoek, as
and hazardous	environment	place. The generation of waste should be	well as Rent-A-Drum, collect (wheely bins and
		avoided as far as practicable; where it	skips, respectively) and remove waste from the
		cannot be avoided, waste should be	Concrete Batch Plant in Newcastle Street,
		reduced, re-used and recovered (including	Northern Industrial Area, Windhoek (Mr Wilfried
		recycling and composting) (e.g. set up collection points for the recycling of solid	Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
		waste); where waste cannot be reduced, re-	Namibia Construction (Pty) Ltd, pers. comm.).
		used and/or recovered, it should be	
		disposed of in an environmentally sound	
		manner.	
		Institute and maintain good housekeeping	N/A (Currently); Compliant (when NC was
		and operating practices; littering is not	operational in the area). Solid waste was
		allowed.	removed from the site and disposed of at NC's
			Concrete Batch Plant in Newcastle Street,
			Northern Industrial Area, Windhoek (for ultimate
			disposal at the Windhoek landfill) (Maartens,
			2017).
		Waste generated during construction	N/A (Currently); Compliant (when NC was
		should not be disposed/stored near any	operational in the area).
		surface water source in the area. Generators to be placed on concrete	N/A (Currently)
		slabs/tarpaulin sails (if applicable).	TVA (Currently)
		Runoff from areas where surface water	
		might have become contaminated should	
		be captured and treated in accordance with	
		the MAWF's Water Quality Standards for	
		Effluent (2008); uncontaminated runoff	
		should be diverted around areas where	
		such water might become contaminated.	
		Contaminated water should not be allowed	
		to enter the Usip River or its tributaries.	
		Non-hazardous and hazardous waste to be	
		collected and stored separately. Non-hazardous waste: refuse (that will not	
		be recycled) to be stored in covered refuse	
		bins, collected on a regular basis and	
		disposed of at the Windhoek Landfill.	
		Hazardous waste: recycle petroleum (fuels	
		and lubricants) waste products and collect	
		and recycle batteries and print cartridges (if	

Impact	Mitigation & Management Measures	Compliance & Comments
	relevant). The remainder to be transported to the hazardous waste disposal site in Windhoek.	
ution of biophysical ironment	Pit latrines to be provided by NC and used by the staff.	N/A (Currently). At the time of operation, there was one pit latrine; 20 kg of builder's lime was added to the pit latrine at the start and the pit latrine was treated with a chemical toilet cleaner (Taurus-range) on a two-weekly basis afterwards (Maartens, 2017).
	Sanitary wastewater to be released into a French drain system.	N/A (Currently)
	Ensure that the discharge of sanitary wastewater to land conform to the regulatory requirements (MAWF's Water Quality Standards for Effluent, 2008).	
ution of biophysical ironment	Ensure that the discharge of process wastewater and/or sanitary wastewater and/or wastewater from utility operations and/or stormwater to land conform to the regulatory requirements (MWAF, 2008). Runoff from areas where surface water	N/A (Currently)
	might have become contaminated should be captured and treated in accordance with the MAWF's Water Quality Standards for Effluent (2008); uncontaminated runoff should be diverted around areas where such water might become contaminated.	
erosion	Regular inspection and maintenance of permanent erosion and runoff control features.	N/A (Currently)
uarrying for Construction Ma	terials on the Remainder of Portion 9 of Farn	n Krumhuk No. 30: Rehabilitation &
ial and Environmental formance	Ensure that the Rehabilitation Plan is implemented (see Maartens, 2017: Annexure G – Kolberg, 2016b). Rehabilitation to take place on a continuous basis. Drill dust to be raked into already disturbed areas (e.g. tracks), or the dust to be removed to a dump site. If water is struck while drilling, a sump must be built to capture the mud; the water must be left to evaporate: salt crusts must then	N/A (Currently)
		Drill dust to be raked into already disturbed areas (e.g. tracks), or the dust to be removed to a dump site. If water is struck while drilling, a sump must

Aspect	Impact	Mitigation & Management Measures	Compliance & Comments
		removed.	
		Return overburden to mined-out quarry (to	
		prevent the accumulation of exposed,	
		stagnant water) and rehabilitate (the mined-	
		out quarry).	
		Disturbed areas to be backfilled with rocks	
		and subsoil, and then the topsoil/vegetation	
		layers.	
		Manually rip (using picks or rakes)	
		disturbed areas where compaction has	
		taken place; avoid creating parallel furrows	
		(this will promote erosion).	
		Reshape all disturbed areas to their original	
		contours / manually rip disturbed areas,	
		where compaction has taken place.	
		Manually remove all weedy / invasive alien	
		species that are present at the site.	
		Adequately drain pipelines and tanks prior	
		to decommissioning (to avoid pollution of	
		the biophysical environment (soil and	
		groundwater)).	
Decommissioning	Social and Environmental	Clean out the oil traps, seal all petrol,	N/A (Currently)
	Performance	diesel, oil and grease containers and	
		remove these from the site(s) to the	
		hazardous waste facility in Windhoek.	
		Remove all equipment, waste, temporary	
		structures, etc. from the site(s).	
		Inform the Ministry of Environment and	
		Tourism to assess the rehabilitation effort	
		for approval and signoff.	

^{*}The Department of Water Affairs (DWA), Ministry of Agriculture, Water and Rural Development (MAWRD) prepared Water Quality Guidelines and these were adopted in 1998 (MAWRD, 1998). In 2008, draft (Water Quality Guidelines and Standards for Potable Water, as well as) Water Quality Standards for Effluent were prepared (Ministry of Agriculture, Water and Forestry (MAWF)) to become Regulations under the Water Resources Management Act 24 of 2004.

2.3 Compliance: Monitoring and Reporting

In order to illustrate Namibia Construction's compliance with the proposed "monitoring and reporting" (see Maartens, 2017), the following colour codes were applied:

Compliance/Completed	
In Progress/Ongoing	
Non-compliance	
Not Applicable	
Changes made to existing EMP	

Туре	Parameter	Frequency	Compliance
River morphology	Volume of sand removed	Monthly (before the 7 th of each month; as per conditions to the authorization granted by the Ministry of Agriculture Water and Forestry for the removal of sand from the Usip River	N/A (10,000-12,000 cubic metres (m³) only were removed by Namibia Construction (Pty) Ltd (NC))
River morphology	Volumes of sand replenished and mined, including cumulative impacts	Annual	N/A
Changes in bed elevation and channel morphology, and riparian habitat upstream and downstream of the in-stream mining site	See Department of Irrigation and Drainage (DID), Ministry of Natural Resources and Environment Malaysia (2009)	Annual and Long-Term Monitoring Programme (if the agreement (for the removal of sand) between Mr Ulf-Dieter Voigts and Namibia Construction (Pty) Ltd is extended)	N/A
Water consumption	Volume of water consumed	Monthly (and if consumption exceeds 20 cubic centimetres (cm³) per month, record the reason)	N/A (around 2 m³ of water per week only was needed (mainly for use by NC's security guard that stayed at the laydown area))
Stormwater and soil erosion	Soil erosion rates	Ad hoc (rainy season)	N/A (NC's activities in the area were short- lived)
Environmental	Environmental performance /	Internal audits (monthly)	N/A (NC's activities in the area were short- lived)
Management Plan	corrective measures to be taken as or when required	External audits (annual)	N/A (NC's activities in the area were short- lived)

Once Namibia Construction resumes their activities in the area (i.e. sourcing material from the Proposed Borrow Pit and Proposed "New" Borrow Pit, and possibly Exploration and Quarrying for Construction Materials), it is advised that Namibia Construction implements the recommendations related to "monitoring and reporting".

2.4 Compliance: Conditions attached to the ECC for Sand Mining

In order to illustrate Namibia Construction's compliance with the "Conditions attached to the ECC" (see Annexure A), the following colour codes were applied:

Compliance/Completed	
In Progress/Ongoing	
Non-compliance	
Not Applicable	
Changes made to existing EMP	

Condition	Compliance
In the case of private land not owned by the lease holder an affidavit should be obtained regarding consent of the concerned land owner (s) for carrying out the mining operation.	See Maartens (2017an agreement for the removal of sand during the period 01 September 2015 until 31 August 2017 is in place between Mr Ulf-Dieter Voigts (representing and managing 21 Krumhuk for Agricultural and Social Development) and Namibia Construction (Pty) Ltd (NC)).
	Compensation is paid to Mr Voigts monthly; NC is in the process of negotiating a new contract / agreement with Mr Voigts (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Valid permit from the Relevant Competent Authority to be obtained for riverbed sand mining, vegetation clearing of protected plant species and boreholes drilling prior to commencement of the project.	An application for a Sand Mining Permit was submitted by Namibia Construction (Pty) Ltd (NC) to the Permanent Secretary, Ministry of Agriculture Water and Forestry (MAWF) on 20 October 2016, again on 21 November 2016, and again on 01 August 2017.
	A representative from NC followed up with Mr Franciskus Witbooi, Deputy Director Law Administration, MAWF in person on 19 February 2020 and was informed that the MAWF has not been issuing separate Permits for Sand Mining for the last few years (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.). No vegetation has been cleared / protected plant species
	removed. No boreholes have been drilled.
All conditions provided by the Relevant Competent Authority with regards to riverbed sanding mining must be complied with.	Ongoing
The Holder shall erect a signboard not smaller than 70 cm in height and 100 cm in width, at the major entrance/s to each of its Sand Mining Site /Area, specifying the duration of the ECC validity and the name of the ECC holder, and a contact name and number for enquiries.	
Mining shall be done in layers of 1 m depth to avoid ponding effect and after first layer is excavated, the process will be repeated for the next layers; All possible precaution as identified in the Environmental Management Plan shall be complied with to prevent and mitigate potential impacts.	N/A
No exposure of groundwater should take place in respect of sand mining activities undertaken within a riverbed.	N/A; also see Maartens (2017: Annexure E - Botha and Van der Merwe (2016) - Depth to groundwater level in the area has an average depth of 40 mbs with some shallower water levels along the banks of the Usip River. Boreholes have an average yield of 4 m³/h and are drilled to an average depth of 75 m).
Depending upon the location, thickness of sand, deposition, agricultural land/river bed, the method of mining may be manual, semi-mechanized or mechanized; however, manual method of mining shall be preferred over any other method.	The method of mining was mechanised.

The ECC holder shall keep a correct account of quantity of sand mined out, dispatched from the site, mode of transport, registration number of vehicle, person incharge of vehicle and site plan. This should be produced before inspectors at any time.	Logs of the loads of material transported to NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek were kept. Note that there is still some material stockpiled at the laydown area (that will be removed at a later stage; see Figure 3) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Restricted working hours: sand mining operation has to be carried out between 7 am to 5 pm.	
Pollution due to dust, exhaust emission or fumes during mining and processing phase should be controlled and kept in permissible limits specified under environmental laws.	
Restoration of flora affected by mining should be done immediately. Twice the number of trees destroyed by mining be planted preferably of indigenous species.	N/A
No overhangs shall be allowed to be formed due to mining and mining shall not be allowed in areas where subsidence of rocks is likely to occur due to steep angle of slope.	N/A
No extraction of stone / boulder / sand in landslide prone areas.	N/A
Dumping of waste shall be done in earmarked places as approved in the plan.	All solid waste was removed from the site and disposed of at NC's Concrete Batch Plant in Newcastle Street, Northern Industrial Area, Windhoek (for ultimate disposal at the Windhoek landfill). Note that there is still some material stockpiled at the laydown area (that will be removed at a later stage; see Figure 3) (Mr Wilfried Schmidt, Contract Manager, Civil Division, Namibia Construction (Pty) Ltd, pers. comm.).
Sand mining sites should not be located within 100 meters from the edge of National Highway and railway line, 60 meters from water reservoir, 25 meter from the edge of other roads except on special exemption from relevant authority.	N/A
Junction at take-off point approach road with main road be properly developed with proper width and geometry required for safe movement of traffic by lease holder at his own cost.	See Maartens (2017: Annexure C - Letter from the Chief Executive Officer, Roads Authority, 21 August 2016). Permission was also given to NC by TransNamib Holdings Ltd for a temporary level crossing at km 243.07 for 5 years (letter from the Executive: Engineering and Technical Services, 09 February 2017).

Once Namibia Construction resumes their activities in the area (i.e. sourcing material from the Proposed Borrow Pit and Proposed "New" Borrow Pit, and possibly Exploration and Quarrying for Construction Materials), it is advised that Namibia Construction adheres to the conditions attached to the (renewed) ECC for sand mining.

3 Conclusions and Recommendations

Namibia Construction's activities in the area have been very limited since 2017. Once the Company resumes their activities (i.e. sourcing material from the Proposed Borrow Pit and Proposed "New" Borrow Pit, and possibly Exploration and Quarrying for Construction Materials), the following is advised:

Namibia Construction (Pty) Ltd and their employees should implement and observe the Environmental Management Plan, including the recommendations related to "monitoring and reporting", and especially the Rehabilitation Plan (see Kolberg 2016a, b), on an ongoing basis.

All conditions attached to the (renewed) ECC should also be implemented and observed.

Environmental performance should be regularly monitored (so that the lessons learnt can be incorporated into the improvement of the Environmental Management Plan over time) and corrective measures taken as or when required.

Dr Lima Maartens

LM Environmental Consulting

4 References

- Botha, P. and J.A. van der Merwe. 2016. Farm Krumhuk No. 30 Sand and Gravel Mining Hydrogeology Specialist Study. Prepared for LM Environmental Consulting. 26 pp.
- Department of Irrigation and Drainage (DID). Ministry of Natural Resources and Environment. Malaysia. 2009. *River Sand Mining Management Guideline*. 85 pp.
- Government of the Republic of Namibia (GRN). 2012. Ministry of Environment and Tourism. Government Notice No. 28. Commencement of the Environmental Management Act, 2007. Government Notice No. 29. List of activities that may not be undertaken without Environmental Clearance Certificate: Environmental Management Act, 2007. Government Notice No. 30. Environmental Impact Assessment Regulations: Environmental Management Act, 2007. Government Gazette of the Republic of Namibia. No. 4878. 6 February 2012.
- International Finance Corporation (IFC). World Bank Group. 2007a. *Environmental, Health, and Safety General Guidelines*. 99 pp.
- International Finance Corporation (IFC). World Bank Group. 2007b. *Environmental, Health, and Safety General Guidelines for Mining.* 33pp.
- Kolberg, H. (Herta Kolberg Botanical Consulting). 2016a. *Krumhuk Sand Mining and Quarrying for Construction Materials. Vegetation Study*. Prepared for LM Environmental Consulting. 23 pp.
- Kolberg, H. (Herta Kolberg Botanical Consulting). 2016b. *Krumhuk Rehabilitation Plan.* Prepared for LM Environmental Consulting. 10 pp.
- Maartens, L. (LM Environmental Consulting). 2017. Environmental Scoping and Management Plan for the Mining of Sand and Quarrying for Construction Materials by Namibia Construction (Pty) Ltd on the Remainder of Portion 9 of Farm Krumhuk No. 30, Khomas Region, Namibia. Prepared for Namibia Construction (Pty) Ltd. 64 pp (plus 8 Annexures).
- Ministry of Agriculture, Water and Rural Development (MAWRD). Department of Water Affairs. 1998. The Water Act (Act 54 of 1956) and its requirements in terms of water supplies for drinking water and for waste water treatment and discharge. 6 pp.
- Prospectors and Developers Association of Canada (PDAC). 2009. Excellence in Environmental Stewardship e-toolkit (EES) Version-01. 309 pp.

5 Annexure A



MINISTRY OF ENVIRONMENT AND TOURISM

Tel: (00 26461) 284 2111 Fax: (00 26461) 229 936

Cnr Robert Mugabe & Dr Kenneth Kaunda Street Private Bag 12306 Windhoek Nambia

E-mail: hiskia inbura ölmet gov.na Enquiries: Mr. Hiskia Mbura

05 June 2017

OFFICE OF THE ENVIRONMENTAL COMMISSIONER

Mr W. J. Schmidt The Director Namibia Construction (Pty) Ltd P. O. Box 5092 Windhoek, 9000

Dear Mr Schmidt

SUBJECT: ENVIRONMENTAL CLEARANCE CERTIFICATE FOR MINING OF SAND AND QUARRYING FOR CONSTRUCTION MATERIALS BY NAMIBIA CONSTRUCTION PTY LTD ON THE REMAINDER OF PORTION 9 OF FARM KRUMHUK NO. 30, KHOMAS REGION

The Environmental Scoping Report and Environmental Management Plan submitted are sufficient as it made provisions of the environmental management concerning the project's activities. From this perspective regular environmental monitoring and evaluations on environmental performance should be conducted. Targets for improvements should be established and monitored throughout this process.

This Ministry reserves the right to attach further legislative and regulatory conditions during the operational phase of the project. The Environmental Clearance Ce tificate is issued with the conditions in Appendix A printed overleaf.

On the basis of the above, this letter serves as an environmental clearance for mining of sand and quarrying for construction materials on the Remainder of Portion 9 of farm Krumhuk No. 30. However, this clearance letter does not in any way hold the Ministry of Environment and Tourism accountable for misleading information, nor any adverse effects that may arise from these activities. Instead, full accountability rests with Namibia Construction (Pty) Ltd and its consultants.

This environmental clearance is valid for a period of 3 (three) years, effective from the date of issue unless withdrawn by this office.

| P/Bag 13300 | P/

Yours sincerely,

7

2017 -05- 0.5

Teofilus Nghitila

ENVIRONMENTAL COMMISSIONER

"Stop the poaching of our rhinos"

APPENDIX A - CONDITIONS ATTACHED TO ENVIRONMENTAL CLEARANCE CERTIFICATE FOR SAND MINING

- In the case of private land not owned by the lease holder an affidavit should be obtained regarding consent of the concerned land owner (s) for carrying out the mining operation.
- Valid permit from the Relevant Competernt Authority to be obtained for riverbed sand mining, vegetation clearing of protected pla species and boreholes drilling prior to commencement of the project.
- All conditions provided by the Relevant Competent Authority with regards to riverbed sanding mining must be complied with.
- 4. The Holder shall erect a signboard not smaller than 70 cm in height and 100cm in width, at the major entrance/s to each of its Sand Mining Site /Area, specifying the duration of the EC validity and the name of the EC holder, and a contact name and number for enquiries.
- Mining shall be done in layers of 1 m depth to avoid ponding effect and after first layer is
 excavated, the process will be repeated for the next layers; All possible precausion as
 identified in the Environmental Management Plan shall be complied with to prevent and
 mitigate potential impacts.
- No exposure of groundwater should take place fin respect of Sand mining activities undertaken within a riverbed.
- Depending upon the location, thickness of sand, deposition, agricultural land/river bed, the method of mining may be manual, semi-mechanized or mechanized; however, manual method of mining shall be preferred over any other method.
- The EC holder shall keep a correct account of quantity of sand mined out, dispatched from the site, mode of transport, registration number of vehicle, person in-charge of vehicle and site plan. This should be produced before inspectors at any time.
- Restricted working hours: Sand mining operation has to be carried out between 7 am to 5 pm.
- Pollution due to dust, exhaust emission or fumes during mining and processing phase should be controlled and kept in permissible limits specified under environmental laws.
- Restoration of flora affected by mining should be done immediately. Twice the number of trees destroyed by mining be planted preferably of indigenous species;
- 12. No overhangs shall be allowed to be formed due to mining and mining shall not be allowed in areas where subsidence of rocks is likely to occur due to steep angle of slope.
- 13. No extraction of stone / boulder / sand in !andslide prone areas.
- 14. Dumping of waste shall be done in carma-ked places as approved in the plan;
- 15. Sand mining sites should not be located within 100 meters from the edge of National Highway and railway line, 60 meters from water resavoir, 25 meter from the edge of other roads except on special exemption from relevant authority.
- Junction at take-off point approach road with main road be properly developed with proper width and geometry required for safe movement of traffic by lease holder at his own cost.