



# **WITVLEI WATER SUPPLY SCHEME**

**ENVIRONMENTAL MANAGEMENT PLAN** 

Date: September 2020 Prepared by:

NamWater, Private Bag 13389, Windhoek, Namibia Contact Person: N.P du Plessis

Tel: +264-6171 2093

Email: Plessisn@namwater.com.na

# **Table of Contents**

LIS	T OF A	BBREVIATIONS	III		
1.	PURP	OSE OF THE EMP	4		
2.	INTRODUCTION		5		
3.	EXISTING WITVLEI WATER SUPPLY INFRASTRUCTURE				
	3.1	Water Source	6		
	3.2	Water Quality and Disinfection	6		
	3.3	Pipe Work	6		
	3.4	Reservoirs	6		
	3.5	Power Supply and Control System	7		
	3.6	Scheme Processes/Operation	7		
	3.7	Maintenance	7		
	3.7.1	Pumps	7		
	3.7.2	Air Valves	7		
	3.7.3	Pressure Gauges and Transducers	7		
	3.7.4	Reservoirs	7		
	3.7.5	Pipe Breaks/leaks	7		
4.	BRIEF DESCRIPTION OF THE RECEIVING ENVIRONMENT10				
	4.1	Climate	.10		
	4.1.1	Precipitation	. 10		
	4.1.2	Temperature	. 10		
	4.2	Geology	.10		
	4.3	Natural Fauna and Flora	.10		
5.	THE L	EGAL ENVIRONMENT	.11		
	5.1	The Constitution of the Republic of Namibia	.11		
	5.2	Environmental Assessment Policy (1995)	.11		
	5.3	Environmental Management Act (No 7 of 2007) (EMA)	.11		
	5.4	EIA Regulations Government Notice No. 30, promulgated on 6 February 2012	.12		
	5.5	Water Act 54 of 1956 and Water Resources Management Act 11 of 2013	.12		
6.	RESPONSIBLE PARTIES				
7.	ENVIF	RONMENTAL MANAGEMENT PLAN	.14		
8.	MANAGEMENT ACTIONS1				
	8.1	Operation and Maintenance phase of the Witvlei Water Supply Scheme	.15		
	8.1.1	Introduction	.15		
	8.2	Maintenance Procedures	.17		
	8.3	Facility Management and Operations			
	8.4	Routine Maintenance and Repairs			
	8.5	Environmental Awareness	.17		
	8.6	Waste and Pollution Management	.17		

	8.6.1	Waste and Pollution Prevention	.17
	8.6.2	Hazardous Materials	.18
	8.6.3	Noise Management	.18
	8.7	Health and Safety	.18
9.	SITE (	CLOSURE AND REHABILITATION	.20
10.	NAMV	ATER ENVIRONMENTAL CODE OF CONDUCT	.21
11.	REFE	RENCES	.26
INA	NEXUR	E 1: GRIEVANCE PROCEDURE AND REGISTRATION FORM	.27

# **LIST OF ABBREVIATIONS**

AIDS Acquired Immune Deficiency Syndrome

**CoC** Code of Conduct

DEA Directorate of Environmental Affairs
EMA Environmental Management Act
EMP Environmental Management Plan
HIV Human Immunodeficiency Virus
I&AP Interested and Affected Parties
MET Ministry of Environment and Tourism
NEM NamWater Environmental Manager

MSDS Material Safety Data Sheet

NWQGNWQSNamibian Water Quality GuidelinesNamibian Water Quality StandardsSTI'sSexually Transmitted Infections

WTW Water Treatment Works

### 1. PURPOSE OF THE EMP

This Environmental Management Plan (EMP) has been compiled and updated for the management of potential environmental impacts during the operation, and decommissioning phases of the existing Witvlei Water Supply Scheme. Best practice is proposed for the generic issues of construction management and supervision as well as the on-going management and operation of the water supply scheme.

In terms of the Environmental Assessment Policy of 1994 and the Environmental Management (Act No 7 of 2007) (EMA), the activities required for the construction of the proposed project requires authorization from the Directorate of Environmental Affairs at the Ministry of Environmental and Tourism (MET: DEA).

An Environmental Clearance Certificate (ECC) was originally issued in 2017 and this EMP serves as an application for the renewal of the ECC.

# 2. INTRODUCTION

Witvlei is a village located in the Omaheke Region, approximately 160 km east of Windhoek. It is a groundwater scheme supplying potable water to the Witvlei Village Council, an abattoir, a tannery and private consumers.

Grünental-Witvlei is a groundwater scheme supplying mainly Witvlei since 2009 (and also Gobabis when required) with potable water. The scheme also supplies the Omaheke Regional Council and local water committees. The location of Witvlei is depicted in **Figure 1.** 

The EMP is for an existing scheme and it is therefore only for the operation and maintenance of the scheme.




Figure 1: Witvlei Location Map

### 3. EXISTING WITVLEI WATER SUPPLY INFRASTRUCTURE

#### 3.1 Water Source

### 3.1.1 Witylei

The Witvlei water supply scheme consists of four boreholes (WW 1176, WW 9287, WW 10223 and WW 100016). These boreholes pump water into a 1 000 m³ concrete ground reservoir from where it is distributed into the reticulation system.

The Witvlei boreholes are between 31.1 m and 60 m deep. The three operational boreholes yield 6 m³/h, 6 m³/h and 3 m³/h respectively.

#### 3.1.2 Grünental-Witvlei

Grünental-Witvlei scheme supplies groundwater to Witvlei (during water shortages from local boreholes) and Gobabis municipality during periods of surface water shortages as well as a few private consumers. The scheme consists of three boreholes (WW 16923, WW 10371 and WW 10228) which pump water into the Otjivero-Gobabis pipeline when raw water is not being transferred between Otjivero and Gobabis. This source can also be used to supply Witvlei in case of water shortages at the Witvlei scheme (which was the case at the time of the site inspection).

The boreholes are between 72 m deep and 77 m deep. The yields of the boreholes vary between 5 m<sup>3</sup>/h and 6 m<sup>3</sup>/h.

A schematic layout of the existing infrastructure is indicated in Figure 2 and 3 below.

### 3.2 Water Quality and Disinfection

The quality of water supplied to Witvlei was evaluated for compliance with the NWQS and the NWQG. According to the NWQG the water can be classified as Group B (Appendix).

An inline chlorination system is installed at the boreholes.

### 3.3 Pipe Work

#### 3.3.1 Witylei

The pipeline consists of approximately 2 000 m of 160 mm diam. uPVC pipe, approximately 1 100 m of 150 mm diam. GMS pipe and 2 100 m of 100 mm diam. GMS pipe.

The theoretical pipe capacity at a velocity of 1 m/s for the 100 mm diam. pipes is 28.3 m³/h and for the 150 mm diam. GMS and 160 mm diam. uPVC pipes 63.6 m³/h.

#### 3.3.2 Grünental-Witylei

The pipe work from the boreholes to the reservoirs consists of approximately 600 m of 90 mm diam. uPVC CL10, 500 m of 200 mm diam. FC CL12, 4 200 m of 250 mm diam. FC CL12 and is reported to be in reasonable condition and no major leakage or pipe bursts occur on these lines.

The theoretical pipe capacities at a velocity of 1 m/s for the 90 mm diam. uPVC, 200 mm diam. FC, 250 mm diam. are 18 m³/h, 100 m³/h and 150 m³/h respectively.

### 3.4 Reservoirs

The storage facilities consist of a 5 m high, 1 000 m³ concrete ground reservoir. The reservoir was secured and permanently closed.

# 3.5 Power Supply and Control System

#### 3.5.1 Witylei

The three operational boreholes with electrical submersible pump installations can be operated in manual or automatic modes. These boreholes are currently operated in automatic mode with a point to point telemetry system installed.

Each of these boreholes has a MCC. Electric power to the boreholes is supplied from pole-mounted transformers each with a 3~phase kWh meter in a meter kiosk. Electricity is supplied by NamPower.

#### 3.5.2 Grünental-Witylei

The Grünental-Witvlei Boreholes scheme is linked to the Gobabis area office via telemetry and can be monitored and controlled remotely. At the time of the site inspection the telemetry system was out of operation and the boreholes were controlled with timers and set to pump to their recommended maximum safe yield hours.

Each of the boreholes is equipped with a MCC. Electric power to the boreholes is supplied from pole-mounted transformers each with a 3~phase kWh meter in a meter kiosk. Electricity is supplied by NamPower.

### 3.6 Scheme Processes/Operation

There is one fulltime NamWater operator based in Witvlei.

#### 3.7 Maintenance

Maintenance is done by a permanent NamWater team.

#### 3.7.1 **Pumps**

All motors bearings should be lubricated with a high-temperature lithium-based grease after 3000 hours.

If a pump/s were out of operation for six months, lubrication is required before service commence on all motor bearings.

#### 3.7.2 Air Valves

The valves must be opened monthly to be descaled and cleaned to ensure effective operation. The service intervals will depend on the severity of the conditions.

### 3.7.3 Pressure Gauges and Transducers

The gauge cocks must be turned monthly to bleed-off air and ensure accurate readings. Turning prevents scale accumulation which prevents the gauge cock from functioning. The operational or service intervals will depend on the severity of the conditions.

#### 3.7.4 Reservoirs

The reservoirs should be checked for leaks and other damages on a monthly basis. If leaks are detected, it should be fixed immediately.

#### 3.7.5 Pipe Breaks/leaks

Monthly monitor of pipes should be done to avoid wastage of water in an event a major pipe break. The pipeline corridor for maintenance work is 10 m by 5 m.




Figure 2: Witvlei Scheme Layout




Figure 3: Grünental Scheme Layout

### 4. BRIEF DESCRIPTION OF THE RECEIVING ENVIRONMENT

The baseline description provided below focuses on the receiving environment:

### 4.1 Climate

Most of the rain in the Omaheke region falls as thundershowers in the summer months, from October to March. Witvlei has an extreme climate most times of the year with high temperatures especially during the rainy season and low temperature during the dry winter season, which is typical of central eastern Namibia.

### 4.1.1 Precipitation

Witvlei has a sub-arid climate with an average annual rainfall ranging from 350-400 mm. Evaporation in this area is between 1700-1900 mm per year (Mendelsohn *et al.*, 2002).

## 4.1.2 Temperature

The mean maximum temperature in the summer months in Witvlei ranges between 32-34°C. The mean minimum temperature in the winter months ranges between 2-4 °C, but it can drop below zero (Mendelsohn *et al.*, 2002).

# 4.2 Geology

The geology in the Witvlei area is made up of Kamtsas quartzite (Damara Sequence) and sediments of the Kuibis Subgroup (Nama Group), locally overlain by tillite and shale of the Dwyka Formation (Karoo Sequence). The fractured aquifers tapped by the various wellfields have moderate to high yields and receive fairly regular recharge (Christelis and Struckmeier 2011:89).

The water scheme for the village of Witvlei draws water from fractured limestone of the Kamtsas Formation along the White Nossob River. The river provides recharge ensuring a plentiful groundwater supply.

#### 4.3 Natural Fauna and Flora

Several species of fauna are found around in the Buitepos surrounds such as kudu (*Tragelaphus strepsiceros*), oryx (*Oryx gazella*), black wildebeest (*Connochaetes gnou*), waterbuck (*Kobus ellipsiprymnus*), springbok (*Antidorcas marsupialis*), duiker (*Sylvicapra grimmia*), black-backed jackal (*Canis mesomelas*), Warthog (*Phacochoerus africanus*), eland (Taurotragus oryx), Burchells zebra (*Equus quagga burchellii*), blue wildebeest (*Connochaetes taurinus*), hartebeest (*Alcelaphus buselaphus*), black faced impala (*Aepyceros melampus petersi*), steenbuck (*Raphicerus campestris*), African wild cat (*Felis silvestris lybica*), and the Namaqua sandgrouse (Pterocles namaqua) (Simmons *et al.*, 1998).

Witvlei is found within the Acacia Tree Shrub Biome, which is characterised by large, open-expanses of grasslands dotted with *Acacia* trees (Mendelsohn *et al.*, 2002). The tree and shrub savanna biome support a moderate to high species diversity, which includes the protected Aloe species (*Aloaceae*) and other endemics. Much of the area contains the *Acacia hereroensis* as well as short bushland with mesic grassland species, such as *Themeda triandra*, *Brachiaria serrata* (Mendelsohn *et al.*, 2009).

Other grass species include the common species *Stipagrostis uniplumis*, *Eragrostis nindensis*, *Microchloa caffra* and *Monelytrum luederitzianum*. A conspicuous part of this vegetation type is the dwarfshrub species *Leucosphaera bainsii* (wolbos), and the *Ericephalus luederitzianus* (kappokbos) (Mendelsohn *et al.*, 2009). *Acacia mellifera* dominates undulating lands; other dominant species are *A. hebeclada* subsp. *hebeclada*, *Catophractes alexandri* (trumpet thorn).

### 5. THE LEGAL ENVIRONMENT

A legal review was done and the key laws of concern include those which protect the ecological integrity of the Witvlei ecosystem and its water resource, including the Water Act of 1954 and the Water Resources Management Act of 2004, and applicable international treaties such as the Convention on Biological Diversity. These laws and conventions place Namibia under an obligation to conserve the ecological integrity of the Witvlei ecosystem for the sustainable use by Namibians.

# 5.1 The Constitution of the Republic of Namibia

There are two clauses contained in the Namibian Constitution that are of particular relevance to sound environmental management practice, viz. articles 91(c) and 95(l). In giving effect to articles 91(c) and 95(l) of the Constitution of Namibia, general principles for sound management of the environment and natural resources in an integrated manner have been formulated. The formulation of these general principles resulted in the Namibia's Environmental Assessment Policy of 1994. To give statutory effect to this Policy, the Environmental Management Act was approved in 2007, and gazetted as the Environmental Management Act (Act No. 7 of 2007) (herein referred to as the EMA. As the organ of state responsible for management and protection of its natural resources, MET: DEA is committed to pursuing the 13 principles of environmental management that is set out by Part 2 of the Act.

To summarise, Articles 91(c) and 95(l) refer to:

- > Guarding against over –utilisation of biological natural resources:
- ➤ Limiting over-exploitation of non-renewable resources;
- > Ensuring ecosystem functionality
- Protecting Namibia's sense of place and character;
- Maintaining biological diversity and
- Pursuing sustainable natural resource use.

### 5.2 Environmental Assessment Policy (1995)

Cabinet endorsed Namibia's Environmental Assessment Policy in 1995 as the first formal effort in Namibia to regulate the application of environmental impact assessments and environmental management. Amongst others, the Policy provides a procedure for conducting EIA's which sets out to:

- > Better inform decision makers and to promote accountability of decisions taken;
- Strive for a high degree of public participation and involvement of all sectors of the Namibian community during the execution of the EIA;
- > Take into account the environmental costs and benefits of projects and Programmes;
- Promote sustainable development in Namibia;
- Ensure that anticipated adverse impacts are minimized and that positive impacts are maximized.

# 5.3 Environmental Management Act (No 7 of 2007) (EMA)

The Environmental Management Act (EMA) was promulgated in 2007 by Parliament and gives effect to the Environmental Assessment Policy. The Act specifies the environmental assessment procedures to be followed as well as the listed activities (activities that require an EIA).

Of relevance to this project are the following listed activities, as provided in Section 27 of this Act, which include:

- Water use and disposal;
- > Transportation

# 5.4 EIA Regulations Government Notice No. 30, promulgated on 6 February 2012

The regulations, promulgated in terms of the EMA, were promulgated on 6 February 2012 and indicated certain activities that require an Environmental Clearance from MET: DEA prior to commencing.

# 5.5 Water Act 54 of 1956 and Water Resources Management Act 11 of 2013

The Water Resources Management Act 11 of 2013 is presently without regulations; therefore the Water Act 54 is still in force. The Act provides for the management and protection of surface and groundwater resources in terms of utilisation and pollution.

### 6. RESPONSIBLE PARTIES

NamWater's Environmental Manager is primarily responsible for the implementation of the EMP during the operational and maintenance phases.

#### 6.1 NamWater

NamWater, as the implementing agency, is responsible for:

- Ensuring that the management actions are being adhered to;
- Ensuring that all environmental impacts are managed according to the environmental principles of avoiding, minimizing, mitigating and rehabilitation. This will be achieved by successful implementation of the EMP;
- Ensuring that appropriate monitoring and compliance auditing are executed;
- Ensuring that the environment is rehabilitated to its natural state as far as possible.

NamWater shall ensure that all employees attend an Environmental, Awareness Training Course. This course shall be structured to ensure that attendees:

- Become familiar with the environmental controls contained in the EMP;
- Are made aware of the need to conserve water and minimise waste:
- Are made aware of NamWater's Code of Conduct;
- Are aware that a copy of the EMP is readily available at the plant and that all staff are aware of the location and have access to the document;
- Are informed that employee information posters, outlining the environmental "do's" and "don'ts" (as per the environmental awareness training course) will be placed at prominent locations throughout the site.

### 7. ENVIRONMENTAL MANAGEMENT PLAN

An Environmental Management Plans (EMP) is an important tool focusing on the management actions that are required to ensure environmental compliance of a particular project.

EMP implementation is a cyclical process that converts mitigation measures into actions and through cyclical monitoring, auditing, review and corrective action, ensures conformance with stated EMP aims and objectives. Monitoring and auditing, feedback for continual improvement ensures that environmental performance has been provided and corrective action is taken for an effective EMP.

The main aim of this EMP is to ensure that the project complies with the goals of the Namibian Environmental Management Act (No. 7 of 2007); and, more specifically, to provide a framework for implementing the management actions as described in the EMP for the operational and maintenance phases of the scheme. Best practice is proposed for the operation of the scheme.

There are some environmental impacts that cannot be avoided. These environmental impacts require mitigation, and in order to mitigate against these impacts an EMP is required. The EMP aims to ensure best practises are implemented and environmental degradation is avoided through appropriate environmental protection, adherence to legal requirements and maintaining good community relationships.

MET indicated that EMP's for existing operations are sufficient.

The project activities are grouped according to the different operational processes and stages. Most of the impacts can be reduced through good housekeeping.

### 8. MANAGEMENT ACTIONS

# 8.1 Operation and Maintenance phase of the Witvlei Water Supply Scheme

### 8.1.1 Introduction

The Operational Phase Section relates to the management and mitigation measures required to ensure that the continuation of the bulk water supply network and the maintenance of the infrastructure is operated in a manner that demonstrates responsible, precautionary environmental management.

The EMP will address specific areas of concern in terms of the long-term environmental management of the affected environment and is intended to serve as a guide to the on-going management of the water supply scheme site as well as the affected environment. The EMP will therefore aim to provide NamWater with the necessary tools to ensure that the potential impacts on the natural environment of the site during the operation of the water supply scheme are minimised. Moreover, it will aim to ensure that the infrastructure is operated and maintained according to Best Practice, in an environmentally sensitive and sustainable manner, and that the operation of the infrastructure does not result in reasonably avoidable environmental impacts.

**Table 1: Operation and Maintenance Phase Management Table** 

Issue	Objective	Strategy	Actions Time frame
Maintenanc e and emergency procedures	To ensure correct procedures are in place to avoid environmental impacts associated with maintenance activities as well as proactive intervention to avoid, and if required, to respond to emergencies	<ul> <li>Establish environmentally sensitive and technically sound maintenance procedures as well as reporting structures.</li> <li>Compile a staff competency assessment and training programme.</li> <li>Establish emergency procedures to ensure appropriate response and minimise potential risk to the biophysical and social environment.</li> </ul>	on maintenance  2. Undertake regular inspection and maintenance of all infrastructure to ensure in working order and to assess damaged / deficient equipment, as per the O&M Manual.  3. Review, and if necessary, revise maintenance manual.  4. Establish emergency procedures guidelines for the blockage/failure, flooding, contaminant removal and inspection and Bi-monthly for the lifespan of infrastructure as per the maintenance manual.  Bi-monthly for the lifespan of infrastructure as per the maintenance manual.  Bi-annually for lifespan of works.  When emergency incident occurs.

#### **8.2 Maintenance Procedures**

The optimal operation and effective maintenance of all the scheme components is important in protecting the environment and ensuring that resources are not wasted and environmental incidents arising out of equipment or infrastructure failures, are avoided. Operation and Maintenance Manuals are available for the Witvlei Water Treatment Works (WTW). The manuals provide a detailed guidance on the operation of all machinery and associated systems as well as related maintenance procedures, including maintenance schedules. Implementation of this manuals by NamWater will facilitate the proactive management of potential risks and thus result in impacts on the receiving environment being averted.

The maintenance procedures set out in the manuals, provides specific guidance in terms of the monitoring and maintenance of the scheme components. These procedures will specify the equipment item and specific component of each piece of equipment requiring checking, the scope and nature of the check that is to be carried out including detailed instructions related to the specific check, and the programme for conducting each check.

# **8.3 Facility Management and Operations**

NamWater shall ensure that sufficient budget allocations and provisions are made available to ensure that the infrastructure can be adequately operated and maintained. NamWater must also attend to damage to the scheme components resulting in water loss as a matter of high priority.

# 8.4 Routine Maintenance and Repairs

The condition of the infrastructure shall be inspected routinely and a maintenance list compiled. Identified, preventative maintenance issues shall be undertaken as soon as possible. Any wastes arising from the repair and maintenance work must be removed and disposed-off at a designated waste deposal site as part of the operation.

### **8.5 Environmental Awareness**

Instilling a sense of environmental awareness and consideration in all employees, but especially those involved with the scheme operations is vital to the overall success of any environmental management plan. It is therefore recommended that a general environmental awareness course for the Scheme Staff Members, who may be required to carry out duties on the scheme, be undertaken.

### **8.6 Waste and Pollution Management**

# 8.6.1 Waste and Pollution Prevention

To prevent the improper disposal of waste and to prevent pollution, the following management actions shall be enforced:

- All waste will be removed to an appropriate waste dump.
- No waste should be buried.
- General Waste: Includes waste paper, plastic, cardboard, harmless organic (e.g. vegetables) and domestic waste.
- No littering will be allowed. The plant area will be kept free of waste at all times.
- Provide sufficient waste bins at worksites. Make sure that all waste is removed from the worksites.

- Hazardous Substances include: sewerage, fuels, lubrication oils, hydraulic and brake fluid, solvents, paints, anti-corrosives, insecticides and pesticides, chemicals, acids etc. It should be disposed of at designated hazardous disposal sites.
- Contaminated soil should be stored in drums and taken to the nearest appropriate waste dumpsite.
- Do not change oil on uncovered ground. Drip trays will be used to catch oil when vehicles are repaired in the field.
- Used oil and hydraulic fluids will not be discarded on the soil or buried. It will be removed from site and taken back to an appropriate dump.
- In the event of a hazardous spill:
  - ✓ Immediately implement actions to stop or reduce the spill.
  - ✓ Contain the spill.
  - ✓ Arrange implementation of the necessary clean-up procedures.
  - ✓ Collect contaminated soil, water and other materials and dispose it at an appropriate waste dumpsite.
- Used solvents and grease should be stored in drums or other suitable containers. It should be sealed and recycled or disposed at an appropriate disposal site.
- Hazardous waste should not be burnt.
- Bunding, concrete slabs and/or other protective measures should be installed where hazardous materials are handled.
- Ensure that the staff are informed and have information pertaining to the management of spills or ingestion.

#### 8.6.2 Hazardous Materials

Where hazardous materials are required for repair and maintenance work (including fuels and oils), care will be taken to ensure that a competent individual is appointed to enforce the responsible use of such materials. The operational staff or maintenance teams shall carry a copy of the relevant Material Safety Data Sheet (MSDS) whenever using such materials. The Scheme Supervisor shall ensure that persons working with hazardous materials have been trained in the handling of such substances, as well as in emergency procedures to be followed in the event of an accidental spillage or medical emergency. Maintenance teams shall also carry a spill kit containing the appropriate neutralizing chemicals, absorbent materials and other relevant equipment required to undertake a clean-up of any spill that may occur.

### 8.6.3 Noise Management

During maintenance operations, all silencing mechanisms on all equipment must be in a good state of repair. Except for in emergency situations, no amplified sound may be broadcast. All routine maintenance shall be restricted to daylight hours.

# 8.7 Health and Safety

To minimise the risk of HIV infection and the increase of STI's and the occurrence injuries the following management actions shall be enforced:

Provide an AIDS awareness programme to all the staff.

- Make sure that all staff are equipped and know how to use safety and protective gear.

  This includes hard hats, goggles, hearing protectors, dusk masks, steel-toed shoes etc.
- Keep a comprehensive first aid kit at Scheme.
- Establish an emergency rescue system for evacuation of serious injured people.
- Emergency procedures for accidents should be communicated to all employees.
- Dangerous areas must be clearly marked and access to these areas controlled or restricted.
- Good driving and adherence to safety rules will result in a minimum number of road and workplace accidents.
- Fire extinguishers must be available at all refuelling sites. Staff should be trained to handle such equipment.
- Nobody is allowed to dispose a burning or smouldering object in an area where it may cause the ignition of a fire.
- Hazardous substances must be kept in adequately protected areas to avoid soil, air or water pollution.
- Work areas, such as these for the maintenance of equipment, must be on concrete slabs.
- Explosives should be stored according to the prescribed regulations.

### 9. SITE CLOSURE AND REHABILITATION

Rehabilitation is the process of returning the land in a given area that has been disturbed by construction and earthworks to some degree of its former state, or an otherwise determined state. Many projects, if not all, will result in the land becoming degraded to some extent. However, with proper rehabilitation most impacts associated with the reservoir construction project, could be mitigated and restored to an acceptable level. Poorly rehabilitated construction areas provide a difficult legacy issue for governments, communities and companies, and ultimately tarnish the reputation of operators as a whole.

Objectives of proper site closure and rehabilitation include the following:

- Reduction or elimination of the need for a long-term management program to control and minimise the long-term environmental impacts;
- Clean-up, treatment or restoration of contaminated areas (e.g. soils contaminated by oil or fuel spills, concrete spills, etc.). Excavation of contaminated material and disposal thereof in an acceptable manner.

### Rehabilitation measures to implement:

- a. A site inspection will be held quarterly by the scheme supervisor after every maintenance work during operation of the scheme. Rehabilitation will be done to the satisfaction of the ENV section and MET.
- b. Frequent inspections of the scheme and effective follow-up procedures, to prevent minor defects from becoming major repair jobs.
- c. Make sure all soil polluted during maintenance work is properly stored in drums and removed to an appropriate waste dump.
- d. Make sure all windblown litter is removed once maintenance has seized.
- e. Make sure that all potential hazards (i.e. the sewerage pit) are properly closed and left in a safe and neat position.

Rehabilitation will be completed when the above have be achieved.

# 10. NAMWATER ENVIRONMENTAL CODE OF CONDUCT

#### What is an Environmental Code of Conduct?

It is a set of rules that everybody has to follow in order to minimise damage to the environment.

#### What is the ENVIRONMENT?

The ENVIRONMENT means the surroundings within which people live. The ENVIRONMENT is made up of the **soil**, **water**, **plants**, and **animals** and those characteristics of the soil, water, air, and plant and animal life that influence **human health and well-being**. **People** and **all human activities** are also part of the environment and have to be considered during the operation of the Scheme.

# Do these ENVIRONMENTAL RULES apply to me?

YES, The Environmental Rules apply to EVERYBODY. This includes all permanent, contract, or temporary workers as well as any other person who visits the Scheme. Every person will be required to adhere to the Environmental Code of Conduct.

# ALL PERSONNEL must study and keep to the Environmental Code of Conduct

The SCHEME SUPERVISOR will issue warnings and will discipline ANY PERSON who breaks any of the Environmental Rules. Repeated and continued breaking of the Rules will result in a disciplinary enquiry and which may result in that person being asked to leave the Scheme permanently.

# What if I do not understand the ENVIRONMENTAL RULES?

ASK FOR ADVICE, if any member of the WORKFORCE does not understand, or does not know how to keep any of the Environmental Rules, that person must seek advice from the SCHEME SUPERVISOR. The PERSON that does not understand must keep asking until he/she is able to keep to all the Environmental Rules.

### Safety and Security

- 1. Only enter and exit roadways and construction areas at demarcated entrances.
- 2. Wear protective clothing and equipment as per signboards at the Scheme and according to instructions from your SCHEME SUPERVISOR.
- 3. Report to your SCHEME SUPERVISOR if you see a stranger or unauthorised person in the construction area.
- 4. Never enter any area that is out of bounds or that is demarcated as dangerous without permission of your SCHEME SUPERVISOR.
- 5. Never climb over any fence or enter private property without permission of the landowner or your SCHEME SUPERVISOR.
- 6. Do not remove any vehicle, machinery, equipment, or any other object from the construction site without the permission of your SCHEME SUPERVISOR.
- 7. Keep clear of blasting sites. Follow the instructions of your SCHEME SUPERVISOR.
- 8. Never enter or work in the Scheme while under the influence of alcohol or other intoxicating substances.

9. All staff should know the emergency procedures in case of accidents.

### **Waste Disposal**

- 10. Learn the difference between different types of waste, namely:
  - general waste, and
  - hazardous waste.

Containers will be provided for different types of wastes.

<u>General Waste</u> includes waste paper, plastic, cardboard, harmless organic (e.g. Vegetables) and domestic waste

<u>Hazardous Waste</u> includes objects, liquids or gases that are potentially dangerous or harmful to any person or the environment. Sewage, fuel, tyres, diesel, oils, hydraulic and brake fluid, paints, solvents, acids, soaps and detergents, resins, old batteries, etc. are all potentially hazardous.

- 11. Learn how to identify the containers for the different types of wastes. Only throw general waste into containers, bins or drums provided for general waste.
- 12. Recycle drums, pallets and other containers.
- 13. Never bury or burn any waste on site, all waste is to be disposed in allocated refuse disposal containers, bins or bags.
- 14. Never overfill any waste container. Inform your SCHEME SUPERVISOR if you notice a container that is nearly full.
- 15. Do not litter.
- 16. Do not bury litter or rubbish in the backfill trench.

#### **Plants and Animals**

- 21. **Do not ever pick any plants, or catch any animal.** People caught with plants or animals in their possession will be handed to the authorities for prosecution.
- 22. Never feed, tease, play with, or set devices to trap any animal or livestock. Wild animals are not to be domesticated.
- 23. Keep off the rock outcrops unless given specific permission by the SCHEME SUPERVISOR to be there.
- 24. Never cut down any tree or branches for firewood.
- 25. Never leave rubbish or food scraps or bones where it will attract animals, birds, or insects.
- 26. Rubbish must be thrown into allocated waste disposal bins/bags.
- 27. Always close the gates behind you.

### **Preventing Pollution**

- 28. Only work with hazardous materials in bunded areas.
- 29. Never discard any hazardous substances such as fuel, oil, paint, solvent, etc. into stream channels or onto the ground. Never allow any hazardous substances to soak into the soil.
- 30. Clean up spills immediately.
- 31. Immediately report to your SCHEME SUPERVISOR when you spill, or notice any hazardous substance overflow, leak or drip or spill on site, into the streambeds or along the road.
- 32. Immediately report to your SCHEME SUPERVISOR when you notice any container, which holds hazardous substances overflow, leak or drip. Spillage must be prevented.
- 33. Only wash vehicles, equipment and machinery, containers and other surfaces at work site areas designated by your SCHEME SUPERVISOR.
- 34. Do not change oil on uncovered surfaces.
- 35. If you are not sure how to transport, store, use, or get rid of any hazardous substances ask your SCHEME SUPERVISOR for advice.

#### Health

- 36. Drink lots of clean water every day.
- 37. Use toilets that have been provided.
- 38. Take the necessary precautions to avoid contracting HIV / AIDS. Condoms are available at most Clinics.
- 39. Inform your SCHEME SUPERVISOR when you are sick.
- 40. Do not work with any machinery when you are sick.
- 41. If you are working in malaria areas, you must take the necessary precautions.

#### **Dust Control**

- 42. Do not make any new roads or clear any vegetation unless instructed to do so by your SCHEME SUPERVISOR.
- 43. Keep to established tracks and pathways.
- 44. Keep within demarcated work areas.

### **Saving Water**

- 47. Always use as little water as possible. Reduce, re-use and recycle water.
- 48. Never leave taps or hose pipes running. Close all taps after use.

49. Report any dripping or leaking taps and pipes to your SCHEME SUPERVISOR.

# **Working Hours**

50. You may only work on weekends and after hours with the consent of the SCHEME SUPERVISOR.

# **Archaeological and Cultural Objects**

- 52. If you find any archaeological, cultural, historical or pre-historical object on the construction site you must immediately notify your SCHEME SUPERVISOR.
- 53. Never remove, destroy, or disturb any cultural, historical, or pre- historical object on site.

<u>Cultural and Historical</u> Objects include old buildings, graves or burial sites, milestones, old coins, beads, pottery and military objects.

<u>Pre-Historical objects</u> include fossils and old bones, old human skeletal remains, pieces of pottery and old tools and implements.

### **Sensible Driving**

- 54. Tracks and roads should be kept to a minimum. Where possible follow existing roads.
- 55. No off-road driving is allowed.
- 56. Never drive any vehicle without a valid licence for that vehicle class and do not drive any vehicle that is not road-worthy.
- 57. Never drive any vehicle when under the influence of alcohol.
- 58. **Always** keep your headlights on when driving on dusty roads.
- 59. Keep to the roads as specified by your SCHEME SUPERVISOR. Vehicles may only be driven on demarcated construction roads. Drivers should always use three points turns, "uturns" are not allowed. Do not cut corners.
- 60. Do not drive on rocky outcrops.

#### Noise

- 61. Keep noise levels as low as possible.
- 62. Do not operate noisy equipment outside normal working hours.

# **Fire Control**

- 63. Do not make open fires, use a drum or tin and do not collect any vegetation to burn.
- 64. Do not smoke or make fires near refuelling depots or any other area where fuel, oil, solvents, or paints are used or stored. Fireplaces should be at a safe distance from fuel and explosive storage sites as well as vehicle parking sites.
- 65. Cigarette butts should always be thrown in allocated refuse bins. Make sure that the cigarette butt is out before throwing it into the bin.
- 66. Immediately notify your SCHEME SUPERVISOR if you see an unsupervised fire at the campsite or construction site.

### **Dealing with Environmental Complaints**

67. If you have any complaint about dangerous working conditions or potential pollution to the environment, talk to your SCHEME SUPERVISOR.

68. If any person complains to you about noise, lights, littering, pollution, or any harmful or dangerous condition, immediately report this to your SCHEME SUPERVISOR.

NP du Plessis Tell: 061-71 2093 Cell: 081 127 9040


OR

Jolanda Murangi Tell: 061-71 2105 Cell: 081 144 1528

# 11.REFERENCES

- 1. Barnard, P., C.J. Brown, A.M. Jarvis, and A. Robertson. 1998. Extending the Namibian protected areas network to safeguard hotspots of endemism and diversity. Biodiversity and Conservation 7: 31-547.
- 2. Christelis, G., and Struckmeier, W. (Eds.). 2011. Groundwater in Namibia an explanation to the Hydrogeological Map. Windhoek
- 3. Department of Water Affairs and Forestry. 2005. Environmental Best Practice Specifications: Construction. Pretoria.
- 4. Department of Water Affairs and Forestry. 2005. Environmental Best Practice Specifications: Site Management and Rehabilitation. Pretoria.
- 5. Goldblatt, P., P. Bernhardt, and J.C. Manning. 1998. Pollination of petaloid geophytes by monkey beetles (Scarabaenidae: Rutelinae: Hopliini) in southern Africa. Annals of the Missouri Botanical Garden 85: 215-230.
- 6. Mendelsohn, J., Jarvis, A., Roberts, C. & Robertson, T. 2002. Atlas of Namibia: a portrait of the land and its people. Ministry of Environment & Tourism / David Philip: Cape Town.
- 7. Mendelsohn, J., Jarvis, A., Roberts, C., & Robertson, T. 2009. Atlas of Namibia: A portrait of the land and its people. Cape Town, South Africa: Sunbird Publishers (PTY) LTD.
- 8. Simmons, R. E., M. Griffin, R. E. Griffin, E. Marais, and H. Kolberg. 1998. Endemism in Namibia: patterns, process and predictions. Biodiversity and Conservation 7: 513-530.

# **ANNEXURE 1: GRIEVANCE PROCEDURE AND REGISTRATION FORM**



# Grievance Registration

Grievance Registration					
Case No:	Date:				
Name of complainant:	Cell no:				
	Email address:				
Details of grievance: (Date, location, persons involved, frequency of occurrence, effects or ensuing situation, etc)					
Name of person recording grievance:	Cell number:				
Proposed date of response:	,				
Signature of recording person:	Signature of complainant:				
Date of redress:					
Decision and action:					